

SPAN Listing No. : 300-10/614/A/W-5

Supplier : **UNITED DUCTILE INDUSTRIES SDN BHD - 785316-T**
NO. 42, JALAN LAYANG-LAYANG 4 BANDAR PUCHONG JAYA PUCHONG 47100 PUCHONG SELANGOR DARUL EHSAN Tel: 60358826277 /Fax: 60358826244

Manufacturer : SHANDONG JIANHUA VALVE MANUFACTURING CO., LTD BAICHIHE INDUSTRIAL PARK ZHUCHENG SHANDONG, CHINA

Principal : UNITED DUCTILE INDUSTRIES SDN BHD NO. 42, JALAN LAYANG-LAYANG 4 BANDAR PUCHONG JAYA PUCHONG 47100 PUCHONGSELANGOR DARUL EHSAN

Category : A (WATER)

Group : CONVEYANCE OF WATER

Product : FITTINGS

Type : DUCTILE IRON (DI) FITTINGS

Sub-type : NA

Details Information :

Model	Series	Description
ALL FLANGED TEE	SERIES: A	PRESSURE RATING : PN10 NOMINAL DIAMETER (mm): 700x200, 700x400, 700x700, 800x200, 800x400, 800x600, 800x800, 900x200, 900x400, 900x600, 900x900, 1000x200, 1000x400, 1000x600, 1000x1000, 1100x400, 1100x600, 1200x600, 1200x800, 1200x1000, 1400x600, 1400x800, 1400x1000, 1500x600, 1500x1000, 1600x600, 1600x800, 1600x1000, 1600x1200, 1800x600, 1800x800, 1800x1000, 1800x1200, 2000x600, 2000x1000 AND 2000x1400 INTERNAL LINING : FUSION BONDED EPOXY OR CEMENT MORTAR (>50MPa) EXTERNAL COATING: FUSION BONDED EPOXY OR BITUMEN
ALL FLANGED TEE	SERIES: A	PRESSURE RATING : PN16 NOMINAL DIAMETER (mm): 350x60, 350x80, 350x100, 350x150, 350x200, 350x250, 350x350, 400x800, 400x100, 400x150, 400x200, 400x250, 400x300, 400x400, 450x100, 450x150, 450x200, 450x250, 450x300, 450x400, 450x450, 900x100, 500x200, 500x400, 500x500, 600x200, 600x400 AND 600x600 INTERNAL LINING : FUSION BONDED EPOXY OR CEMENT MORTAR (>50MPa) EXTERNAL COATING: FUSION BONDED EPOXY OR BITUMEN
ALL FLANGED TEE	SERIES: A	PRESSURE RATING : PN25 NOMINAL DIAMETER (mm): 40x40, 50x50, 60x40, 60x60, 65x65, 80x40, 80x60, 80x80, 100x40, 100x60, 100x80, 100x100, 125x40, 125x60, 125x80, 125x100, 125x125, 150x40, 150x60, 150x80, 150x100, 150x125, 150x150, 200x40, 200x60, 200x80, 200x100, 200x125, 200x150, 200x200, 250x60, 250x80, 250x100, 250x150, 250x200, 250x250, 300x60, 300x80, 300x100, 300x150, 300x200, 300x250 AND 300x300 INTERNAL LINING : FUSION BONDED EPOXY OR CEMENT MORTAR (>50MPa) EXTERNAL COATING: FUSION BONDED EPOXY OR BITUMEN
ALL SOCKET TEE	SERIES: A	PRESSURE RATING : PN25 NOMINAL DIAMETER (mm): 40x40, 50x50, 60x60, 65x65, 80x40, 80x80, 100x40, 100x60, 100x80, 100x100, 125x40, 125x80, 125x100, 125x125, 150x40, 150x80, 150x100, 150x150, 200x40, 200x80, 200x100, 200x150, 200x200, 250x80, 250x100, 250x150, 250x200, 250x250, 300x100, 300x150, 300x200, 300x250 AND 300x300 INTERNAL LINING : FUSION BONDED EPOXY OR CEMENT MORTAR(>50MPa) EXTERNAL COATING: FUSION BONDED EPOXY OR BITUMEN
BLANK FLANGED	SERIES: A	PRESSURE RATING : PN10 AND PN16 NOMINAL DIAMETER (mm): 40, 50, 60, 65, 80, 100, 125, 150, 200, 250, 300, 350, 400, 450, 500, 600, 700, 800, 900, 1000, 1100, 1200, 1400, 1500, 1600, 1800 AND 2000 INTERNAL LINING : FUSION BONDED EPOXY OR CEMENT MORTAR (>50MPa) EXTERNAL COATING: FUSION BONDED EPOXY OR BITUMEN
BLANK FLANGED	SERIES: A	PRESSURE RATING : PN25 NOMINAL DIAMETER (mm): 40, 50, 60, 65, 80, 100, 125, 150, 200, 250, 300, 350, 400, 450, 500 AND 600 INTERNAL LINING : FUSION BONDED EPOXY OR CEMENT MORTAR (>50MPa) EXTERNAL COATING: FUSION BONDED EPOXY OR BITUMEN

Model	Series	Description
DOUBLE FLANGED 22.5 BEND AND DOUBLE FLANGED 11.25 BEND	SERIES: A	PRESSURE RATING : PN16 NOMINAL DIAMETER (mm): 350 AND 400 INTERNAL LINING : FUSION BONDED EPOXY OR CEMENT MORTAR (>50MPa) EXTERNAL COATING: FUSION BONDED EPOXY OR BITUMEN
DOUBLE FLANGED 45 BEND	SERIES: A	PRESSURE RATING : PN10 NOMINAL DIAMETER (mm): 700, 800, 900, 1000, 1100, 1200, 1400, 1500, 1600, 1800 AND 2000 INTERNAL LINING : FUSION BONDED EPOXY OR CEMENT MORTAR (>50MPa) EXTERNAL COATING: FUSION BONDED EPOXY OR BITUMEN
DOUBLE FLANGED 90 BEND, 90 DUCKFOOT BEND	SERIES: A	PRESSURE RATING : PN10 NOMINAL DIAMETER (mm): : 700, 800, 900 AND 1000 INTERNAL LINING : FUSION BONDED EPOXY OR CEMENT MORTAR (>50MPa) EXTERNAL COATING: FUSION BONDED EPOXY OR BITUMEN
DOUBLE FLANGED 90 BEND, DOUBLE FLANGED 45 BEND,	SERIES: A	PRESSURE RATING : PN16 NOMINAL DIAMETER (mm): 350, 400, 450, 500 AND 600 INTERNAL LINING : FUSION BONDED EPOXY OR CEMENT MORTAR (>50MPa) EXTERNAL COATING: FUSION BONDED EPOXY OR BITUMEN
DOUBLE FLANGED 90 BEND, DOUBLE FLANGED 45 BEND, DOUBLE FLANGED 22.5 BEND, DOUBLE FLANGED 11.25 B	SERIES: A	PRESSURE RATING : PN25 NOMINAL DIAMETER (mm): 40, 50, 60, 65, 80, 100, 125, 150, 200, 250 AND 300 INTERNAL LINING : FUSION BONDED EPOXY OR CEMENT MORTAR (>50MPa) EXTERNAL COATING: FUSION BONDED EPOXY OR BITUMEN
DOUBLE FLANGED TAPPER	SERIES: A	PRESSURE RATING : PN10 NOMINAL DIAMETER (mm): 700x600, 800x700, 900x800, 1000x900, 1100x1000, 1200x1000, 1400x1200, 1500x1400, 1600x1400, 1800x1600 AND 2000x1800 INTERNAL LINING : FUSION BONDED EPOXY OR CEMENT MORTAR (>50MPa) EXTERNAL COATING: FUSION BONDED EPOXY OR BITUMEN
DOUBLE FLANGED TAPPER	SERIES: A	PRESSURE RATING : PN16 NOMINAL DIAMETER (mm): 350x300, 400x300, 400x350, 450x400, 500x400 AND 600x500 INTERNAL LINING : FUSION BONDED EPOXY OR CEMENT MORTAR (>50MPa) EXTERNAL COATING: FUSION BONDED EPOXY OR BITUMEN
DOUBLE FLANGED TAPPER	SERIES: A	PRESSURE RATING : PN25 NOMINAL DIAMETER (mm): 50x40, 60x50, 65x50, 80x60, 80x65, 100x80, 125x100, 150x125, 200x150, 250x200, AND 300x250 INTERNAL LINING : FUSION BONDED EPOXY OR CEMENT MORTAR (>50MPa) EXTERNAL COATING: FUSION BONDED EPOXY OR BITUMEN
DOUBLE SOCKET 90 BEND, DOUBLE SOCKET 45 BEND, DOUBLE SOCKET 22.5 BEND, DOUBLE SOCKET 11.25 BEND	SERIES: A	PRESSURE RATING : PN10 NOMINAL DIAMETER (mm): 700, 800, 900, 1000, 1100, 1200, 1400, 1500, 1600, 1800 AND 2000 INTERNAL LINING : FUSION BONDED EPOXY OR CEMENT MORTAR (>50MPa) EXTERNAL COATING: FUSION BONDED EPOXY OR BITUMEN
DOUBLE SOCKET 90 BEND, DOUBLE SOCKET 45 BEND, DOUBLE SOCKET 22.5 BEND, DOUBLE SOCKET 11.25 BEND	SERIES: A	PRESSURE RATING : PN16 NOMINAL DIAMETER (mm): 350, 400, 450, 500 AND 600 INTERNAL LINING : FUSION BONDED EPOXY OR CEMENT MORTAR (>50MPa) EXTERNAL COATING: FUSION BONDED EPOXY OR BITUMEN
DOUBLE SOCKET 90 BEND, DOUBLE SOCKET 45 BEND, DOUBLE SOCKET 22.5 BEND, DOUBLE SOCKET 11.25 BEND	SERIES: A	PRESSURE RATING : PN25 NOMINAL DIAMETER (mm): 40, 50, 60, 65, 80, 100, 125, 150, 200, 250 AND 300 INTERNAL LINING : FUSION BONDED EPOXY OR CEMENT MORTAR (>50MPa) EXTERNAL COATING: FUSION BONDED EPOXY OR BITUMEN
DOUBLE SOCKET TAPPER	SERIES: A	PRESSURE RATING : PN10 NOMINAL DIAMETER (mm): 700x500, 700x600, 800x600, 800x700, 900x700, 900x800, 1000x800, 1000x900, 1100x1000, 1200x1000, 1400x1200, 1500x1400, 1600x1400, 1800x1600 AND 2000x1800 INTERNAL LINING : FUSION BONDED EPOXY OR CEMENT MORTAR (>50MPa) EXTERNAL COATING: FUSION BONDED EPOXY OR BITUMEN
DOUBLE SOCKET TAPPER	SERIES: A	PRESSURE RATING : PN16 NOMINAL DIAMETER (mm): 350x200, 350x250, 350x300, 400x250, 400x300, 400x350, 450x350, 450x400, 500x350, 500x400, 600x400 AND 600x500 INTERNAL LINING : FUSION BONDED EPOXY OR CEMENT MORTAR (>50MPa) EXTERNAL COATING: FUSION BONDED EPOXY OR BITUMEN

Model	Series	Description
DOUBLE SOCKET TAPPER	SERIES: A	PRESSURE RATING : PN25 NOMINAL DIAMETER (mm): 50x40, 60x50, 65x50, 80x40, 80x60, 80x65, 100x60, 100x80, 125x60, 125x80, 125x100, 150x80, 150x100, 150x125, 200x100, 200x125, 200x150, 250x125, 250x150, 250x200, 300x150, 300x200 AND 300x250 INTERNAL LINING : FUSION BONDED EPOXY OR CEMENT MORTAR (>50MPa) EXTERNAL COATING: FUSION BONDED EPOXY OR BITUMEN
DOUBLE SOCKET TEE WITH FLANGED BRANCH	SERIES: A	PRESSURE RATING : PN10 NOMINAL DIAMETER (mm): 700x200, 700x400, 700x700, 800x200, 800x400, 800x600, 800x800, 900x200, 900x400, 900x600, 900x900, 1000x200, 1000x400, 1000x600, 1000x1000, 1100x400, 1100x600, 1200x600, 1200x800, 1200x1000, 1400x600, 1400x800, 1400x1000, 1500x600, 1500x1000, 1600x600, 1600x800, 1600x1000, 1600x1200, 1800x600, 1800x800, 1800x1000, 1800x1200, 2000x600, 2000x1000 AND 2000x1400 INTERNAL LINING : FUSION BONDED EPOXY OR CEMENT MORTAR (>50MPa) EXTERNAL COATING: FUSION BONDED EPOXY OR BITUMEN
DOUBLE SOCKET TEE WITH FLANGED BRANCH	SERIES: A	PRESSURE RATING : PN16 NOMINAL DIAMETER (mm): 350x60, 350x80, 350x100, 350x150, 350x200, 350x250, 350x350, 400x80, 400x100, 400x150, 400x200, 400x250, 400x300, 400x400, 450x100, 450x150, 450x200, 450x250, 450x300, 450x400, 450x450, 500x100, 500x200, 500x400, 500x500, 600x200, 600x400 AND 600x600 INTERNAL LINING : FUSION BONDED EPOXY OR CEMENT MORTAR (>50MPa) EXTERNAL COATING: FUSION BONDED EPOXY OR BITUMEN
DOUBLE SOCKET TEE WITH FLANGED BRANCH	SERIES: A	PRESSURE RATING : PN25 NOMINAL DIAMETER (mm): 40x40, 50x50, 60x40, 60x60, 65x40, 65x65, 80x40, 80x60, 80x80, 100x40, 100x60, 100x80, 100x100, 125x40, 125x60, 125x80, 125x100, 125x125, 150x40, 150x60, 150x80, 150x100, 150x125, 150x150, 200x40, 200x60, 200x80, 200x100, 200x125, 200x150, 200x200, 250x60, 250x80, 250x100, 250x150, 250x200, 250x250, 300x60, 300x80, 300x100, 300x150, 300x200, 300x250 AND 300x300 INTERNAL LINING : FUSION BONDED EPOXY OR CEMENT MORTAR (>50MPa) EXTERNAL COATING: FUSION BONDED EPOXY OR BITUMEN
FLANGED SOCKET, FLANGED SPIGOT, COLLAR	SERIES: A	PRESSURE RATING : PN10 NOMINAL DIAMETER (mm): 700, 800, 900, 1000, 1100, 1200, 1400, 1500, 1600, 1800 AND 2000 INTERNAL LINING : FUSION BONDED EPOXY OR CEMENT MORTAR (>50MPa) EXTERNAL COATING: FUSION BONDED EPOXY OR BITUMEN
FLANGED SOCKET, FLANGED SPIGOT, COLLAR, 90° DUCKFOOT BEND	SERIES: A	PRESSURE RATING : PN16 NOMINAL DIAMETER (mm): 350, 400, 450, 500 AND 600 INTERNAL LINING : FUSION BONDED EPOXY OR CEMENT MORTAR (>50MPa) EXTERNAL COATING: FUSION BONDED EPOXY OR BITUMEN
FLANGED SOCKET, FLANGED SPIGOT, COLLAR, 90° DUCKFOOT BEND	SERIES: A	PRESSURE RATING : PN25 NOMINAL DIAMETER (mm): 40, 50, 60, 65, 80, 100, 125, 150, 200, 250 AND 300 INTERNAL LINING : FUSION BONDED EPOXY OR CEMENT MORTAR (>50MPa) EXTERNAL COATING: FUSION BONDED EPOXY OR BITUMEN

Brands : UDI

Standard : MS 1919:2013

Certificate body & Certificate No : SIRIM PC003334

Certification Scope : FITTINGS-DUCTILE IRON (DI) FITTINGS-NA

Valid Until : 2024/12/12